

Your country data and more on using R for SAE

Nairobi Workshop: Day 1

Ann-Kristin Kreutzmann

Josh Merfeld

August 26, 2024

Session 1: Country data in R

By you!

Welcome

- Welcome to the first day of the workshop!
- We are going to start with the task you were given as your pre-workshop assignment.

A quick reminder

- What did we ask from you?
1. Describe your country data set, e.g., number of observations and variables, content, sampling design, etc.
 2. Describe the variable of interest, e.g., distribution, missing values, outstanding observations, etc.
 3. Describe variables that you think are related to the variable of interest.
 4. Demonstrate basic visualization of the selected indicators.

Session 2: Hands-on session

Data preparation for SAE

My slides

- Before we get into it, I have put all of my material on the web
- You can find my slides (along with copy-pasteable code) AND the data I'm using on my GitHub repository:
 - <https://github.com/JoshMerfeld/nairobiworkshops>
 - Scroll down to the bottom and you'll find all of the links you'll need.
 - I'd suggest you have these open during the workshop to make things easier.

Let's get started!


- Let's get started with the hands-on session.
- As a first step, I'd like to hear from all of you:
 - How much experience do you have using R?
 - This is all experience, not just with SAE


Some things to note


- We will be using **RStudio** throughout the workshops
 - There are other options you are welcome to use (VS Code is the most common alternative)
- Two general “data cleaning” pipelines:
 - The **tidyverse**
 - The **data.table** package (which builds on base R)
- We will be using the tidyverse

Getting started with RStudio


- Let's start by looking at the layout of RStudio.
- For those of you with ample R experience, nothing here will be new!










Down here you will find
a list of files in your
working directory, as
well as the “viewer” and
help pane



This is the console. Output
appears here. (You can also use
this as a calculator!)







FileEditCodeViewPlotsSessionBuildDebugProfileToolsWindowHelp

RStudio

Go to file/function

Addins

Source on Save

Run

Source

Week 1 - Introduction to R

library(tidyverse)

data

<- read_csv("data.csv")

Environment

History

Connections

R

Global Environment

Data

data

7209 obs. of 10

\$ res_id

\$ ability

\$ age

\$ educyears

\$ isfarmer

\$ yearsfarming

\$ yearsmanagingfarm

\$ outsidewage

\$ worriedaboutcropprices

\$ worriedaboutcrop yields

- attr(*, "spec")=

.. cols(

.. res_id = col_doubl

Files

Plots

Packages

Help

V

applied-microeconometrics > weeks

Name

..

assets

data.csv

header.tex

script.R

week1a.log

week1a.pdf

week1a.Rmd

week1b.log

week1b.pdf

week1b.Rmd

Terminal

Background Jobs

~/Dropbox/KDIS/Classes/applied-microeconometrics/weeks/week1

data

read_csv("data.csv")

Columns: 10

specification

"

educyears, isfarmer, worriedaboutcropprices, worriedaboutcrop yields

res_id, ability, age, yearsfarming, yearsmanagingfarm, outsidewage

ec())` to retrieve the full column specification for this data.

the column types or set `show\_col\_types = FALSE` to quiet this message.

Why don't you all give it a try

- Create a script in RStudio
- Save that script in a specific place (folder) on your computer
 - Make sure to keep track of where you save it!
 - I create a folder for each specific project I work on
 - e.g. you could create “Nairobi Workshops” and save the script as “day1.R”

First things first: the working directory

- The working directory is the folder that R is currently working in
 - This is where R will look for files
 - This is where R will save files
 - This is where R will create files
- You can always write out an entire file path, but this is tedious
 - More importantly, it makes your code less reproducible since the path is specific to YOUR computer

First things first: the working directory

- One nice thing about R is that the working directory will automatically be where you open the script from
 - Let's try this. Save your script to a folder on your computer, then open the script from that folder.
 - Let's see if it worked!

▼ Code

```
1 getwd() # this command will show you your current working directory
```

```
[1] "/Users/Josh/Dropbox/Papers/UN-SAE/workshops/africa/nairobiworkshops"
```

First things first: the working directory

- You can also set the working directory in RStudio
 - Session > Set Working Directory > Choose Directory (or Source File Location)
 - Give it a try and let's see if it worked!

▼ Code

```
1 getwd() # this command will show you your current working directory
```

```
[1] "/Users/Josh/Dropbox/Papers/UN-SAE/workshops/africa/nairobiworkshops"
```

Always use the same working directory!

- Make sure to always set the working directory to the same location when working in the same script!
- This will avoid problems later
 - It also makes your code more reproducible (e.g. if a colleague wants to run it, you just send the entire folder and it works with no changes)

R packages

- R is a language that is built on packages
 - Packages are collections of functions that do specific things
 - R comes with a set of “base” packages that are installed automatically
- We are going to use one package consistently, called the “tidyverse”
 - This consists of a set of packages that are designed to work together, with data cleaning in mind

R packages

The one exception to always using a script? I install packages in the CONSOLE. You can install packages like this:

▼ Code

```
1 install.packages("tidyverse") # this will install the tidyverse package. Note the quotes!
```

- You only need to install a package once on your computer.

R packages

The first thing you'll do in your script is load packages. You do it like this:

▼ Code

```
1  '''  
2  This script is part of the Nairobi Workshop on SAE.  
3  Date: 26 August 2024 (written earlier!)  
4  Author: Josh Merfeld  
5  '''  
6  # Load packages (libraries)  
7  library(tidyverse)
```

- Note that the first part is a comment I've added to the script.
 - I make a lot of comments!

Loading data

- Let's start by loading some data.
 - This is survey data from Tanzania (NPS 5, 2020)
 - It is a list of all individuals in all households in the survey
- Let's load the csv version. Tidyverse has a command for this: `read_csv()`

▼ Code

```
1 # Load packages (libraries)
2 library(tidyverse)
3 # load data
4 df <- read_csv("day1data/tanzanialsms.csv")
```

Looking at the data

- `glimpse` is an easy way to look at the data:

▼ Code

```
1 # Load packages (libraries)
2 library(tidyverse)
3 # load data
4 df <- read_csv("day1data/tanzanialsms.csv")
5 glimpse(df)
```

```
1 Rows: 23,592
2 Columns: 46
3 $ interview__key <chr> "39-26-37-98", "39-26-37-98", "39-26-37-98", "39-26-37-98", "04-06-65-04", "97-90-78-65", "97-90-78-65", "
4 $ y5_hhid <chr> "1000-001-01", "1000-001-01", "1000-001-01", "1000-001-01", "1000-001-02", "1000-001-03", "1000-001-03", "
5 $ y4_hhid <chr> "1000-001", "1000-001", "1000-001", "1000-001", "1000-001", "1000-001", "1000-001", "1000-001", "1000-001"
6 $ indidy5 <dbl> 1, 3, 5, 7, 1, 1, 2, 4, 6, 7, 8, 1, 2, 4, 1, 2, 3, 4, 5, 6, 7, 8, 1, 2, 3, 1, 2, 3, 1, 2, 3, 4, 5, 6, 1, 2
7 $ hh_b01 <chr> "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CON
8 $ hh_b02 <chr> "male", "female", "male", "male", "male", "male", "female", "female", "male", "female", "female", "male", "
9 $ hh_b03_1 <chr> "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CON
10 $ hh_b03_2 <chr> "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CONFIDENTIAL***", "***CON
11 $ hh_b04 <dbl> 74, 44, 35, 9, 47, 36, 42, 21, 1, 1, 6, 32, 32, 2, 48, 45, 23, 21, 17, 14, 8, 2, 79, 71, 34, 63, 41, 22, 4
12 $ hh_b05 <chr> "head", "SON/DAUGHTER", "SON/DAUGHTER", "grandchild", "head", "head", "spouse", "SON/DAUGHTER", "SON/DAUGH
13 $ hh_b06 <chr> "1", "3", "5", "NOT PREVIOUSLY PRESENT", "2", "4", "NOT PREVIOUSLY PRESENT", "NOT PREVIOUSLY PRESENT", "NO
14 $ hh_b07 <chr> "yes", "yes", "no", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "no", "yes", "yes", "yes", "yes", "ye
15 $ hh_b08 <dbl> 31, 31, 0, 31, 31, 31, 31, 31, 31, 31, 31, 31, 31, 31, 31, 31, 0, 31, 31, 31, 31, 31, 31, 31, 31, 31,
16 $ hh_b09_1 <chr> "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "yes", "
17 $ hh_b0a <chr> "yes", "yes", "no", "no", "yes", "yes", "yes", "yes", "yes", "yes", "no", "yes", "no", "yes", "no", "yes", "yes",
```


Data is not always in .csv files

- Sometimes files come in other formats
- I have uploaded a Stata file, as well (tanzanialsms.dta)
 - To read Stata files (common with survey data), we need a different package, called **haven**
 - After we install it, you can load it using **read_dta()**
- Give it a try. Install the package and then load the data.

► Code

But let's use the .csv file for now

▼ Code

```
1 # Load packages (libraries)
2 library(tidyverse)
3 # load data
4 df <- read_csv("dayldata/tanzanialsms.csv")
5 glimpse(df)
```

[illegible]

Objects in memory

- The data frame is a matrix
 - Each row is an observation and each column is a variables
 - You can see it in the “environment” pane of RStudio
- We can also see the names of the columns like this:

▼ Code

```
1 colnames(df)
```

```
1  [1] "interview__key" "y5_hhid"      "y4_hhid"      "indidy5"      "hh_b01"      "hh_b02"      "hh_b03_1"      "hh_b03_2"
```

Calling variables in R

- Some of you might be used to Stata
- One big difference between the two is that Stata generally only has one data frame in memory at a time
 - This means that you can call a variable *without referencing the data frame*
- In R, if you want to look at a variable, you have to tell R which data frame it is in
 - This is done with the `$` operator
 - For example, if I want to look at the variable “age” in the data frame “data”, I would write `data$age`
 - In our dataset, the age variable is `hh_b04`

Summary stats for hh_b04 (age)

- There are two common ways to quickly look at a variable:
 - `summary()`: gives you mean/median, and a few more
 - `table()`: gives you a frequency table

▼ Code

```
1 summary(df$hh_b04)
```

1	Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
2	0.00	8.00	18.00	22.78	33.00	95.00

Summary stats for hh_b04 (age)

- There are two common ways to quickly look at a variable:
 - `summary()`: gives you mean/median, and a few more
 - `table()`: gives you a frequency table

▼ Code

```
1 table(df$hh_b04)
```

```
1  
2  0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31  
3 695 750 721 716 723 597 738 717 623 647 627 619 574 582 571 559 592 546 518 438 519 500 403 397 384 425 379 352 358 323 277 299 2
```


Variable types

- The most common are numeric, character, and logical
 - Numeric variables are numbers
 - For example, the variable `hh_b04` is a numeric variable
 - Missing value: `NA`
 - Character variables are text
 - For example, the variable `y5_hhid` is a character variable
 - Missing value: `""`
 - Logical variables are TRUE/FALSE
 - We don't have any examples here (at least not yet)
 - Missing value: `NA`

Pipes

- One of the most useful things in R is the pipe operator (`|>` or `%>%`)
 - This is part of the tidyverse package
 - It allows you to chain commands together
 - It makes your code much easier to read
 - It makes your code much easier to write
- Let's use it to clean some variables

Pipes example

- I'm going to create some new variables. What do you think this does?

▼ Code

```
1 df <- df |>
2   rename(gender = hh_b02, age = hh_b04) |>
3   mutate(boy = gender=="male" & age<15,
4          girl = gender=="female" & age<15,
5          prime_aged_male = gender=="male" & age>=15 & age<=64,
6          prime_aged_female = gender=="female" & age>=15 & age<=64,
7          elderly_male = gender=="male" & age>64,
8          elderly_female = gender=="female" & age>64)
```

Pipes example

- I'm going to create some new variables. What do you think this does?

▼ Code

```
1 df <- df |>
2   rename(gender = hh_b02, age = hh_b04) |>
3   mutate(boy = gender=="male" & age<15,
4     girl = gender=="female" & age<15,
5     prime_aged_male = gender=="male" & age>=15 & age<=64,
6     prime_aged_female = gender=="female" & age>=15 & age<=64,
7     elderly_male = gender=="male" & age>64,
8     elderly_female = gender=="female" & age>64)
```

- ① Renames the variables `hh_b02` and `hh_b04` to `gender` and `age`, respectively (line 2)
- ② Creates new variables based on the conditions given (lines 3-8)

Pipes example

- Let's look at the resulting variables:

▼ Code

```
1 summary(df[,c("boy", "girl", "prime_aged_male", "prime_aged_female", "elderly_male", "elderly_female")])
```

1	boy	girl	prime_aged_male	prime_aged_female	elderly_male	elderly_female
2	Mode :logical	Mode :logical	Mode :logical	Mode :logical	Mode :logical	Mode :logical
3	FALSE:18687	FALSE:18597	FALSE:17396	FALSE:16988	FALSE:23211	FALSE:23081
4	TRUE :4905	TRUE :4995	TRUE :6196	TRUE :6604	TRUE :381	TRUE :511

- What did I do here?
 - I summarized **df** based on the names of COLUMNS (variables)
 - I did this by creating a vector of column names (as characters)
 - The resulting variables are logical, or True/False
 - Why?

Let's do some more cleaning

- What are some other common data cleaning tasks?
- Some common things:
 - Renaming variables
 - Creating new variables based on existing variables
 - Doing this based on groups
 - Replace values (e.g. replacing missings)
 - i.e. recoding variables

Let's do some more cleaning

- What are some other common data cleaning tasks?
- Some common things:
 - **Renaming variables**
 - **Creating new variables based on existing variables**
 - Doing this based on groups
 - Replace values (e.g. replacing missings)
 - i.e. recoding variables

What do we want to do?

- To do more, we need to look at the survey questionnaire!
 - The data I have uploaded is from Section B
 - You can find the survey questionnaire in the data folder for day 1
- Here's the data:

```
1 # A tibble: 23,592 × 46
2   interview__key y5_hhid      y4_hhid indidy5 hh_b01      hh_b02 hh_b03_1      hh_b03_2      hh_b04 hh_b05      hh_b
3   <chr>          <chr>      <chr>    <dbl> <chr>      <chr>    <chr>          <chr>      <dbl> <chr>      <chr>
4 1 39-26-37-98    1000-001-01 1000-001      1 **CONFIDENTIAL** male   **CONFIDENTIAL** **CONFIDENTIAL**      74 head      1
5 2 39-26-37-98    1000-001-01 1000-001      3 **CONFIDENTIAL** female **CONFIDENTIAL** **CONFIDENTIAL**      44 SON/DAUGHTER 3
6 3 39-26-37-98    1000-001-01 1000-001      5 **CONFIDENTIAL** male   **CONFIDENTIAL** **CONFIDENTIAL**      35 SON/DAUGHTER 5
7 4 39-26-37-98    1000-001-01 1000-001      7 **CONFIDENTIAL** male   **CONFIDENTIAL** **CONFIDENTIAL**      9 grandchild NOT
8 5 04-06-65-04    1000-001-02 1000-001      8 **CONFIDENTIAL** male   **CONFIDENTIAL** **CONFIDENTIAL**      47 head      2
9 6 97-90-78-65    1000-001-03 1000-001      1 **CONFIDENTIAL** male   **CONFIDENTIAL** **CONFIDENTIAL**      36 head      4
10 7 97-90-78-65    1000-001-03 1000-001      2 **CONFIDENTIAL** female **CONFIDENTIAL** **CONFIDENTIAL**      42 spouse     NOT
11 8 97-90-78-65    1000-001-03 1000-001      4 **CONFIDENTIAL** female **CONFIDENTIAL** **CONFIDENTIAL**      21 SON/DAUGHTER NOT
12 9 97-90-78-65    1000-001-03 1000-001      6 **CONFIDENTIAL** male   **CONFIDENTIAL** **CONFIDENTIAL**      1 SON/DAUGHTER NOT
13 10 97-90-78-65    1000-001-03 1000-001      7 **CONFIDENTIAL** female **CONFIDENTIAL** **CONFIDENTIAL**      1 SON/DAUGHTER NOT
14 # i 23,582 more rows
```

SECTION B: HOUSEHOLD MEMBER ROSTER[illegible]

Let's do some cleaning

- Two things:
 - Calculate the education of the head's mother
 - Collapse the data to the HOUSEHOLD level, with the following variables:
 - Number of boys/girls
 - Number of prime-aged males/females
 - Number of elderly males/females
 - The head's gender
- How do we do this?

Let's do some cleaning

- Let's start by loading the data again
 - You might want to try this in a new script so you have a self-contained example of data cleaning
 - Go ahead and load libraries and read the .csv (not .dta) data:

► Code

Back to our task

- Calculate the education of the head's mother
- Collapse the data to the HOUSEHOLD level, with the following variables:
 - Number of boys/girls
 - Number of prime-aged males/females
 - Number of elderly males/females
 - The head's gender
- What are the variables we need? (look at the questionnaire)
 - `y5_hhid` (household identifier)
 - `hh_b02` (gender)
 - `hh_b04` (age)
 - `hh_b05` (relationship to head)

How are we going to do this?

- Create the new variables
 - Boys, girls, prime-aged males, prime-aged females, elderly males, elderly females
 - The head's gender
- Collapse the data to the household level
 - We will want to sum the count variables
 - We will want to take the highest value for the head's gender (since there is only one)

First, rename some variables

▼ Code

```
1 dfhh <- df |>
2   rename(gender = hh_b02, age = hh_b04, relationship = hh_b05) |>
3   select(y5_hhid, gender, age, relationship)
4 head(dfhh)
5 unique(dfhh$relationship)
```

- ① Renames the variables `hh_b02` and `hh_b04` to `gender` and `age`, respectively, as well as relationship to the head
- ② Just keep the variables we want
- ③ Shows us the first few lines
- ④ Unique values for `relationship`

```
# A tibble: 6 × 4
  y5_hhid    gender    age relationship
<chr>      <chr>    <dbl>    <chr>
1 1000-001-01 male      74 head
2 1000-001-01 female    44 SON/DAUGHTER
3 1000-001-01 male      35 SON/DAUGHTER
4 1000-001-01 male        9 grandchild
5 1000-001-02 male      47 head
6 1000-001-03 male      36 head
```

[1] "head"	"SON/DAUGHTER"	"grandchild"	"spouse"	
"OTHER RELATIVE (SPECIFY)"	"OTHER NON- RELATIVES (SPECIFY)"	"FATHER/MOTHER"	"SISTER/BROTHER"	"STEP SON
/ DAUGHTER"	"LIVE-IN SERVANT"			

Now, create new variables (with new **dfhh** object)

▼ Code

```
1 dfhh <- dfhh |>
2   mutate(boy = (gender=="male" & age<15),
3         girl = (gender=="female" & age<15),
4         prime_aged_male = (gender=="male" & age>=15 & age<=64),
5         prime_aged_female = (gender=="female" & age>=15 & age<=64),
6         elderly_male = (gender=="male" & age>64),
7         elderly_female = (gender=="female" & age>64),
8         head_male = ifelse(relationship=="head", gender=="male", NA)) |>
9   select(y5_hhid, boy, girl, prime_aged_male, prime_aged_female, elderly_male, elderly_female, head_male)
```

- ① Creates new variables based on the conditions given (lines 3-8)
- ② Creates head's mother's education variable based on the condition given (line 9)
- ③ Just keep the variables we want

Finally, aggregate to household

▼ Code

```
1 dfhh <- dfhh |>
2   group_by(y5_hhid) |>
3   summarize(boy = sum(boy, na.rm = TRUE),
4             girl = sum(girl, na.rm = TRUE),
5             prime_aged_male = sum(prime_aged_male, na.rm = TRUE),
6             prime_aged_female = sum(prime_aged_female, na.rm = TRUE),
7             elderly_male = sum(elderly_male, na.rm = TRUE),
8             elderly_female = sum(elderly_female, na.rm = TRUE),
9             head_male = max(head_male, na.rm = TRUE))
10 summary(dfhh)
```

y5_hhid	boy	girl	prime_aged_male	prime_aged_female	elderly_male	elderly_female	head_male
Length:4709	Min. : 0.000	Min. : 0.000	Min. :0.000	Min. :0.000	Min. :0.00000	Min. :0.0000	Min. :0.0000
Class :character	1st Qu.: 0.000	1st Qu.: 0.000	1st Qu.:1.000	1st Qu.:1.000	1st Qu.:0.00000	1st Qu.:0.0000	1st Qu.:0.0000
Mode :character	Median : 1.000	Median : 1.000	Median :1.000	Median :1.000	Median :0.00000	Median :0.0000	Median :1.0000
	Mean : 1.042	Mean : 1.061	Mean :1.316	Mean :1.402	Mean :0.08091	Mean :0.1085	Mean :0.7297
	3rd Qu.: 2.000	3rd Qu.: 2.000	3rd Qu.:2.000	3rd Qu.:2.000	3rd Qu.:0.00000	3rd Qu.:0.0000	3rd Qu.:1.0000
	Max. :10.000	Max. :11.000	Max. :8.000	Max. :8.000	Max. :2.00000	Max. :2.0000	Max. :1.0000

Why is this important for SAE?

- You will use this type of aggregation *all* the time in SAE.
- We often model at an aggregate level
 - Could be the household
 - Could be the district
 - Could be the county
 - Etc.
- So bookmark this code!

Now it's your turn!

- Select some variables from the dataset
- Create the following household-level dataset:
 - Total household size
 - Proportion of CHILDREN (<15) who are male
 - Proportion of ADULTS (15+) who are female

Visualization with `ggplot2`

What is ggplot2?

- **ggplot2** is included in the **tidyverse** package
 - It is a package for creating beautiful graphics
 - Let's look at some of the basics
- Let's start over with our .csv file

► Code

Basic syntax for ggplot2?

- The basic syntax is as follows:

```
ggplot() + geom_point(data = df, aes(x = xvar, y = yvar))
```


- Note the use of `+` and not `|>`
- `geom_point` can be replaced with all sorts of “geoms”!
 - `geom_line`
 - `geom_bar`
 - `geom_density` (this will have no)

Let's look at an example

- Let's start with one that is simple to understand
 - How about the distribution of age in the dataset?

▼ Code


```
1 ggplot() +  
2   geom_density(data = df, aes(x = hh_b04))
```



Cleaning it up a bit

▼ Code


```
1 ggplot() +  
2   geom_density(data = df, aes(x = hh_b04)) +  
3   labs(x = "Age", y = "Density")
```



Cleaning it up even more (my favorite “theme”)

▼ Code


```
1 ggplot() +  
2   geom_density(data = df, aes(x = hh_b04)) +  
3   labs(x = "Age", y = "Density") +  
4   theme_bw()
```



What if we want to add by gender?

▼ Code


```
1 ggplot() +  
2   geom_density(data = df, aes(x = hh_b04)) +  
3   labs(x = "Age", y = "Density") +  
4   theme_bw() +  
5   facet_wrap(~hh_b02, ncol = 1)
```



What if we want to add by gender?

▼ Code


```
1 ggplot() +  
2   geom_density(data = df, aes(x = hh_b04)) +  
3   labs(x = "Age", y = "Density") +  
4   theme_bw() +  
5   facet_wrap(~hh_b02, ncol = 2)
```



Putting them on one plot is simple, too!

▼ Code

```
1 ggplot() +  
2   geom_density(data = df,  
3     aes(x = hh_b04, color = hh_b02)) +  
4   labs(x = "Age", y = "Density") +  
5   theme_bw()
```




Cleaning up the legend

- Let's use the `scale_color_brewer` function to clean up the legend (title and colors)

▼ Code


```
1 ggplot() +  
2   geom_density(data = df,  
3     aes(x = hh_b04, color = hh_b02)) +  
4   scale_color_brewer("Gender", palette = "Set2") +  
5   labs(x = "Age", y = "Density") +  
6   theme_bw()
```



Fill instead of color?

▼ Code

```
1 ggplot() +  
2   geom_density(data = df,  
3     aes(x = hh_b04, fill = hh_b02)) +  
4   scale_fill_brewer("Gender", palette = "Set2") +  
5   labs(x = "Age", y = "Density") +  
6   theme_bw()
```




- Note how hard it is to see both!

▼ Code

```
1 ggplot() +  
2   geom_density(data = df,  
3     aes(x = hh_b04, fill = hh_b02),  
4     alpha = 0.5) +  
5   scale_fill_brewer("Gender", palette = "Set2") +  
6   labs(x = "Age", y = "Density") +  
7   theme_bw()
```


- ① Change opacity with **alpha**



Finally, changing the location of the legend!


▼ Code

```
1 ggplot() +  
2   geom_density(data = df,  
3     aes(x = hh_b04, fill = hh_b02),  
4     alpha = 0.5) +  
5   scale_fill_brewer("Gender", palette = "Set2") +  
6   labs(x = "Age", y = "Density") +  
7   theme_bw() +  
8   theme(legend.position = "bottom")
```



▼ Code

```
1 ggplot() +  
2   geom_density(data = df,  
3     aes(x = hh_b04, fill = hh_b02),  
4     alpha = 0.5) +  
5   scale_fill_brewer("Gender", palette = "Set2") +  
6   labs(x = "Age", y = "Density") +  
7   theme_bw() +  
8   theme(legend.position = c(0.9, 0.8))
```




Just FYI, the R Color Brewer palettes

- Here you can see all the color palettes
- Some of these are for continuous variables
- The middle section is mostly for categorical variables (like gender)
- Choose color by changing the PALETTE NAME:

▼ Code

```
1 ggplot() +  
2   geom_density(data = df,  
3     aes(x = hh_b04, fill = hh_b02),  
4     alpha = 0.5) +  
5   scale_fill_brewer("Gender", palette = "PALETTE NAME") +  
6   labs(x = "Age", y = "Density") +  
7   theme_bw() +  
8   theme(legend.position = "bottom")
```



Let's look at another example

- In this example, we'll also practice aggregating to higher levels (again!)
 - Let's look at the proportion of people in agriculture and in education BY AGE GROUP
 - We are going to use the following variables:
 - hh_b04 (age)
 - hh_b11 (main occupation)

▼ Code

```
1 table(df$hh_b11)
```

```
1
2      AGRICULTURE / LIVESTOCK      disabled      EMPLOYED (NOT AG): WITH EMPLOYEES EMPLOYED (NOT AG):
3                        5320                        238                        360
```

- The relevant two values are “AGRICULTURE / LIVESTOCK” and “student”

First, we need to create age groups

- Let's create age groups using the **cut** function
 - This will create a *factor* variable

▼ Code

```
1 df <- df |>
2   mutate(age_groups = cut(hh_b04, breaks = seq(from = 0, to = max(df$hh_b04), by = 5)))
3 head(df$age_groups)
```

① Creates a new variable **age_groups** based on the conditions given (line 3)

```
1 [1] (70,75] (40,45] (30,35] (5,10] (45,50] (35,40]
2 Levels: (0,5] (5,10] (10,15] (15,20] (20,25] (25,30] (30,35] (35,40] (40,45] (45,50] (50,55] (55,60] (60,65] (65,70] (70,75] (75,
```

- The **seq** function creates a sequence of numbers from 0 to the maximum age in the dataset, in increments of 5

Now, let's create the occupation variables

▼ Code

```
1 df <- df |>
2   mutate(ag = ifelse(hh_b11 == "AGRICULTURE / LIVESTOCK", 1, 0),
3     ed = ifelse(hh_b11 == "student", 1, 0))
```

- Now aggregate to `age_groups`

▼ Code


```
1 dfgroups <- df |>
2   filter(!is.na(age_groups)) |>
3   group_by(age_groups) |>
4   summarize(ag = mean(ag, na.rm = TRUE),
5     ed = mean(ed, na.rm = TRUE)) |>
6   ungroup()
```

- ① Removes missing values
- ② Groups by `age_groups`
- ③ Calculates the mean of `ag` and `ed` (removing missing values)
- ④ Ungroups the data frame

Now we can plot them


▼ Code

```
1 ggplot() +  
2   geom_point(data = dfgroups,  
3     aes(x = age_groups, y = ag)) +  
4   labs(x = "Age group",  
5     y = "Proportion of respondents in category") +  
6   theme_bw()
```



▼ Code

```
1 ggplot() +  
2   geom_point(data = dfgroups,  
3     aes(x = age_groups, y = ed)) +  
4   labs(x = "Age group",  
5     y = "Proportion of respondents in category") +  
6   theme_bw()
```




But what if we want to plot them on the same graph?

- This is a little more complicated!
- Look what happens here:

▼ Code

```
1 ggplot() +  
2   geom_point(data = dfgroups,  
3     aes(x = age_groups, y = ag)) +  
4   geom_point(data = dfgroups,  
5     aes(x = age_groups, y = ed)) +  
6   labs(x = "Age group",  
7     y = "Proportion of respondents in category") +  
8   theme_bw()
```




- Do you see the problem?

But what if we want to plot them on the same graph?

- We can specify individual colors.
- Look what happens here:

▼ Code

```
1 ggplot() +  
2   geom_point(data = dfgroups,  
3     aes(x = age_groups, y = ag), color = "navy") +  
4   geom_point(data = dfgroups,  
5     aes(x = age_groups, y = ed), color = "orange") +  
6   labs(x = "Age group",  
7     y = "Proportion of respondents in category") +  
8   theme_bw()
```



- Still a problem! What is it?

Here's the code. Let's discuss!

▼ Code

```
1 library(RColorBrewer)
2 colors <- brewer.pal(3, "Set2")
3 colors
```

```
[1] "#66C2A5" "#FC8D62" "#8DA0CB"
```


▼ Code

```
1 ggplot() +
2   geom_point(data = dfgroups,
3     aes(x = age_groups, y = ag, color = "Ag")) +
4   geom_point(data = dfgroups,
5     aes(x = age_groups, y = ed, color = "Educ.)) +
6   labs(x = "Age group",
7     y = "Proportion of respondents in category") +
8   scale_color_manual("Occupation:",
9     values = c("Ag" = colors[1], "Educ." = colors[2])) +
10  theme_bw()
```

How does it look?


▼ Code

```
1 ggplot() +  
2   geom_point(data = dfgroups,  
3     aes(x = age_groups, y = ag, color = "Ag")) +  
4   geom_point(data = dfgroups,  
5     aes(x = age_groups, y = ed, color = "Educ.")) +  
6   labs(x = "Age group",  
7     y = "Proportion of respondents in category") +  
8   scale_color_manual("Occupation:",  
9     values = c("Ag" = colors[1], "Educ." = colors[2])) +  
10  theme_bw()
```



▼ Code

```
1 ggplot() +  
2   geom_point(data = dfgroups,  
3     aes(x = age_groups, y = ag, color = "Ag")) +  
4   geom_point(data = dfgroups,  
5     aes(x = age_groups, y = ed, color = "Educ.")) +  
6   labs(x = "Age group",  
7     y = "Proportion of respondents in category") +  
8   scale_color_manual("Occupation:",  
9     values = c("Ag" = colors[1], "Educ." = colors[2])) +  
10  theme_bw() +  
11  theme(legend.position = c(0.9, 0.8))
```



What about doing line graphs?

- We have to make a change! We cannot do a line graph with a factor variable!

▼ Code

```
1 ggplot() +  
2   geom_line(data = dfgroups, aes(x = as.numeric(age_groups), y = ag, color = "Ag")) +  
3   geom_line(data = dfgroups, aes(x = as.numeric(age_groups), y = ed, color = "Educ.")) +  
4   scale_x_continuous(breaks = as.numeric(unique(dfgroups$age_groups)), labels = unique(dfgroups$age_groups)) +  
5   labs(x = "Age group", y = "Proportion of respondents in category") +  
6   scale_color_manual("Occupation:", values = c("Ag" = colors[1], "Educ." = colors[2])) +  
7   theme_bw() +  
8   theme(legend.position = c(0.9, 0.8))
```


- ① Turn it into a numeric variable.
- ② Change the x-axis to the numeric values and label it with the original values.

Finally, adding them together!


▼ Code

```
1 ggplot() +  
2   geom_point(data = dfgroups, aes(x = as.numeric(age_groups), y = ag, color = "Ag")) +  
3   geom_line(data = dfgroups, aes(x = as.numeric(age_groups), y = ag, color = "Ag")) +  
4   geom_point(data = dfgroups, aes(x = as.numeric(age_groups), y = ed, color = "Educ.")) +  
5   geom_line(data = dfgroups, aes(x = as.numeric(age_groups), y = ed, color = "Educ.")) +  
6   scale_x_continuous(breaks = as.numeric(unique(dfgroups$age_groups)), labels = unique(dfgroups$age_groups)) +  
7   labs(x = "Age group", y = "Proportion of respondents in category") +  
8   scale_color_manual("Occupation:", values = c("Ag" = colors[1], "Educ." = colors[2])) +  
9   theme_bw() +  
10  theme(legend.position = c(0.9, 0.8))
```


How it looks



What about doing line graphs?



Now it's your turn!

- Select some variables from the dataset
- You need to create the following:
 - A graph with only one variable (e.g. density)
 - A graph with two variables (e.g. point or line)